

# MFX-C5595i

color A3 multifunctional printer



BRIDGE THE GAP  
BETWEEN PAPER AND DIGITAL  
**BUSINESS-CLASS  
DOCUMENT SOLUTIONS**

MFX-*i*INTELLIGENT Series



## CUSTOMER BENEFITS



**Intuitive operability**  
Operate the Muratec MFX like a smartphone or tablet with fully customized user interface



**Mobile connectivity**  
Print anytime from anywhere with Muratec's innovative mobile technologies



**Security**  
Secure network integration, data encryption and advanced user authentication



**Application ecosystem**  
Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio



**Productivity**  
Reliability, high-speed scanning and printing, combined with powerful finishing functions



**Sustainability**  
Numerous eco features reduce energy consumption and costs

## OPTIONS

### 1 ENHANCED FEATURES

- PDF enhancements  
LK-102v3
- OCR text recognition  
LK-105v4
- Barcode fonts  
LK-106
- Unicode fonts  
LK-107
- OCR A and B fonts  
LK-108
- Document converter pack  
LK-110v2
- ThinPrint® client  
LK-111
- Antivirus  
LK-116
- IP fax (T.38 fax)  
LK-117\*



### 2 CONNECTIVITY

- Fax board  
FK-514 x2
- Wireless LAN  
UK-221
- USB I/F kit  
EK-608
- USB I/F kit  
EK-609 OR
- Fiery controller  
IC-420
- Interface kit for IC-420  
VI-516
- Biometric authentication  
AU-102
- ID card reader  
AU-205H OR
- Mount kit  
MK-735

### 3 OTHERS

- Working table  
WT-506
- 10-Key pad  
KP-102
- Security kit  
SC-509
- 1 TB SSD  
EM-908
- Keyboard holder  
KH-102
- External keyboard

**LEGEND**

- Mandatory option
- Option
- This option can only be installed with the respective option above it

### 4 MEDIA INPUT

- 1x Universal tray  
PC-116 OR
- 2x Universal tray  
PC-216 OR
- Large capacity tray  
PC-416 OR
- Large capacity tray  
PC-417 OR
- Copy desk  
DK-516 OR
- Large capacity tray  
LU-302 OR
- Large capacity tray  
LU-207 OR
- Banner tray  
MK-730

\* May not be available at time of launch.

### 5 MEDIA OUTPUT

- |  |   |   |   |
|--|---|---|---|
| <ul style="list-style-type: none"> <li>Output tray<br/>OT-513 <span style="float: right;">OR</span></li> <li>Job separator<br/>JS-508 <span style="float: right;">OR</span></li> </ul> | <ul style="list-style-type: none"> <li>Inner finisher<br/>FS-533 <span style="float: right;">OR</span></li> <li>Attachment kit<br/>MK-607 <span style="float: right;">OR</span></li> <li>Punch kit for FS-533<br/>PK-519</li> </ul> | <ul style="list-style-type: none"> <li>Staple finisher<br/>FS-539 <span style="float: right;">OR</span></li> <li>Relay unit<br/>RU-513 <span style="float: right;">OR</span></li> <li>Booklet finisher<br/>FS-539SD <span style="float: right;">OR</span></li> <li>Relay unit<br/>RU-513 <span style="float: right;">OR</span></li> <li>Punch kit for FS-539/SD<br/>PK-524</li> </ul> | <ul style="list-style-type: none"> <li>Staple finisher<br/>FS-540 <span style="float: right;">OR</span></li> <li>Relay unit<br/>RU-513 <span style="float: right;">OR</span></li> <li>Booklet finisher<br/>FS-540SD <span style="float: right;">OR</span></li> <li>Relay unit<br/>RU-513 <span style="float: right;">OR</span></li> <li>Punch kit for FS-540/SD<br/>PK-526 <span style="float: right;">OR</span></li> <li>Post inserter for FS-540/SD<br/>PI-507 <span style="float: right;">OR</span></li> <li>Job separator for FS-540/SD<br/>JS-602 <span style="float: right;">OR</span></li> <li>Z-fold unit for FS-540/SD<br/>ZU-609</li> </ul> |
|--|---|---|---|

## FINISHING FUNCTIONALITIES

- |                 |                    |                   |                     |        |                           |           |                 |          |         |                |        |                 |                           |
|-----------------|--------------------|-------------------|---------------------|--------|---------------------------|-----------|-----------------|----------|---------|----------------|--------|-----------------|---------------------------|
|                 |                    |                   |                     |        |                           |           |                 |          |         |                |        |                 |                           |
| Corner stapling | Two-point stapling | Two-hole punching | Three-hole punching | Duplex | Combined mixplex/mixmedia | Half-fold | Sheet insertion | Tri-fold | Booklet | Offset sorting | Z-fold | Banner printing | Corner stapling (offline) |

## DESCRIPTION

### ENHANCED FEATURES

<b>LK-102v3 PDF enhancements</b>	PDF/A(1b), PDF encryption, digital signature
<b>LK-105v4 OCR text recognition</b>	Searchable PDF and PPTX
<b>LK-106 Barcode fonts</b>	Supports native barcode printing
<b>LK-107 Unicode fonts</b>	Supports native Unicode printing
<b>LK-108 OCR A and B fonts</b>	Supports native OCR A and B font printing
<b>LK-110v2 Document file conversion</b>	Generates various file formats including DOCX, XLSX and PDF/A
<b>LK-111 ThinPrint client</b>	Print data compression for reduced network impact
<b>LK-116 Antivirus</b>	Bitdefender® antivirus provides real time scanning of all incoming and outgoing data
<b>LK-117 IP fax (T.38 fax)*</b>	Fax over IP networks (T.38), requires fax kit

### CONNECTIVITY

<b>FK-514 Fax board</b>	Super G3 fax, digital fax functionality
<b>UK-221 Wireless LAN</b>	Wireless LAN and wireless LAN Access Point Mode
<b>EK-608 USB I/F kit</b>	USB keyboard connection
<b>EK-609 USB I/F kit</b>	USB keyboard connection, Bluetooth
<b>IC-420 Fiery controller</b>	Professional color print controller
<b>VI-516 Interface kit for IC-420</b>	Fiery controller interface card
<b>AU-102 Biometric authentication</b>	Finger vein scanner
<b>AU-205H ID card reader</b>	Supports various ID card technologies
<b>MK-735 Mount kit</b>	Installation kit for ID card reader

### OTHERS

<b>WT-506 Working table</b>	Authentication device placement
<b>KP-102 10-Key pad</b>	For numeric entry instead of touchscreen
<b>SC-509 Security kit</b>	Copy guard function
<b>EM-908 SSD</b>	1 TB SSD to increase storage space
<b>KH-102 Keyboard holder</b>	To place USB keyboard
<b>External keyboard</b>	Keyboard for alpha numeric data entry

## TECHNICAL SPECIFICATIONS

### SYSTEM SPECIFICATIONS

<b>System speed 8.5" x 11"</b>	Up to 55/55 ppm (mono/color)
<b>System speed 11" x 17"</b>	Up to 27/27 ppm (mono/color)
<b>Auto duplex speed 8.5" x 11"</b>	Up to 55/55 ppm (mono/color)
<b>1st page out time 8.5" x 11"</b>	3.3/4.3 sec. (mono/color)
<b>Warm-up time</b>	Approx. 14/16 sec. (mono/color) <sup>1</sup>
<b>Imaging technology</b>	Laser
<b>Toner technology</b>	Simitri® HD polymerized toner
<b>Panel size/resolution</b>	10.1" / 1,024 x 600
<b>System memory</b>	8 GB (standard/max.)
<b>System hard drive</b>	256 GB SSD (standard) / 1 TB SSD (optional)
<b>Interface</b>	10/100/1,000-Base-T Ethernet, USB 2.0, Wi-Fi 802.11 b/g/n/ac (optional)
<b>Network protocols</b>	TCP/IP (IPv4 / IPv6) / SMB / LPD / IPP / SNMP / HTTP(S) / Bonjour
<b>Automatic document feeder</b>	Up to 300 originals / 5.5" x 8.5" – 11" x 17" / 35–210 g/m <sup>2</sup> / Dualscan ADF
<b>ADF double feed detection</b>	Standard
<b>Printable paper size</b>	3.5" x 5.5" – 12" x 18" / customized paper sizes / banner paper max. 47.2" x 11.7"
<b>Printable paper weight</b>	52–300 g/m <sup>2</sup>
<b>Paper input capacity</b>	1,150 sheets / 6,650 sheets (standard/max.)
<b>Paper tray input (standard)</b>	1 x 500 / 3.5" x 5.8" – 11" x 17" / custom sizes / 52–256 g/m <sup>2</sup> 1 x 500 / 5.5" x 8.5" – 12" x 18" / custom sizes / 52–256 g/m <sup>2</sup>
<b>Paper tray input (optional)</b>	1 x 500 / 5.5" x 8.5" – 11" x 17" / 52–256 g/m <sup>2</sup> 2 x 500 / 5.5" x 8.5" – 11" x 17" / 52–256 g/m <sup>2</sup> 1 x 2,500 / 8.5" x 11" / 52–256 g/m <sup>2</sup> 1 x 1,500 + 1 x 1,000 sheets / 5.5" x 8.5" or 8.5" x 11" / 52–256 g/m <sup>2</sup>

### MEDIA INPUT

<b>PC-116 1x Universal tray</b>	500 sheets / 5.5" x 8.5" – 11" x 17" / 52–256 g/m <sup>2</sup>
<b>PC-216 2x Universal tray</b>	2x 500 sheets / 5.5" x 8.5" – 11" x 17" / 52–256 g/m <sup>2</sup>
<b>PC-416 Large capacity tray</b>	2,500 sheets / 8.5" x 11" / 52–256 g/m <sup>2</sup>
<b>PC-417 Large capacity tray</b>	1,500 + 1,000 sheets / 5.5" x 8.5" or 8.5" x 11" / 52–256 g/m <sup>2</sup>
<b>LU-302 Large capacity tray</b>	3,000 sheets / 8.5" x 11" / 52–256 g/m <sup>2</sup>
<b>LU-207 Large capacity tray</b>	2,500 sheets / 8.5" x 11" – 12" x 18" / 52–256 g/m <sup>2</sup>
<b>MK-730 Banner tray</b>	Multipage banner feeding
<b>DK-516 Copier desk</b>	Provides storage space for print media and other materials

### MEDIA OUTPUT

<b>OT-513 Output tray</b>	Output tray used instead of finisher
<b>JS-508 Job separator</b>	Separation of fax output; etc.
<b>FS-533 Inner finisher</b>	50-sheet stapling, 500 sheets max. output
<b>MK-607 Attachment kit</b>	For FS-533 installation
<b>PK-519 Punch kit for FS-533</b>	2/4 hole punching, auto switching
<b>FS-539 Staple finisher</b>	50-sheet stapling / 3,200 sheets max. output
<b>FS-539SD Booklet finisher</b>	50-sheet stapling / 20-sheet booklet finisher / 2,200 sheets max. output
<b>PK-524 Punch kit for FS-539/SD</b>	2/3 hole punching, auto switching
<b>FS-540 Staple finisher</b>	100-sheet stapling / 3,200 sheets max. output
<b>FS-540SD Booklet finisher</b>	100-sheet stapling / 20-sheet booklet finisher / 2,700 sheets max. output
<b>PK-526 Punch kit for FS-540/SD</b>	2/3 hole punching, auto switching
<b>RU-513 Relay unit</b>	For FS-539/SD or FS-540/SD installation
<b>JS-602 Job separator for FS-540/SD</b>	Separation of fax output, etc.
<b>PI-507 Post inserter for FS-540/SD</b>	Cover insertion, post finishing
<b>ZU-609 Z-fold unit for FS-540/SD</b>	Z-fold for 11" x 17" prints

<b>Large capacity tray (optional)</b>	1 x 3,000 / 8.5" x 11" / 52–256 g/m <sup>2</sup> 1 x 2,500 / 8.5" x 11" – 12" x 18" / custom sizes / 52–256 g/m <sup>2</sup>
<b>Manual bypass</b>	150 sheets / 3.5" x 5.5" – 12" x 18" / custom sizes / banner / 60–300 g/m <sup>2</sup>
<b>Finishing modes (optional)</b>	Offset, Group, Sort, Staple, Staple (offline), Punch, Half-fold, Letter-fold, Booklet, Post insertion, Z-fold
<b>Automatic duplexing</b>	4.1" x 5.5" – 12" x 18" / 52–256 g/m <sup>2</sup>
<b>Output capacity</b>	Up to 250 sheets / up to 3,300 sheets (standard/max.)
<b>Stapling</b>	Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300 g/m <sup>2</sup> )
<b>Stapling output capacity</b>	Max. 200 sets
<b>Letter fold</b>	Max. 3 sheets
<b>Letter fold capacity</b>	Max. 50 sets, unlimited (without tray)
<b>Booklet</b>	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 300 g/m <sup>2</sup> )
<b>Booklet output capacity</b>	Max. 35 booklets, unlimited (without tray)
<b>Duty cycle (monthly)</b>	Max. <sup>2</sup> 200,000 pages
<b>Toner lifetime</b>	Black up to 28,000 pages CMY up to 28,000 pages
<b>Imaging unit lifetime</b>	Black up to 240,000/1,000,000 pages (drum/developer) CMY up to 165,000/1,000,000 pages (drum/developer)
<b>Power consumption</b>	110–120 V / 60 Hz, Less than 1.6 kW
<b>System dimension (W x D x H)</b>	24.2" x 27.1" x 37.8" (without options)
<b>System weight</b>	Approx. 220 lb (without options)

\* May not be available at time of launch.

## PRINTER SPECIFICATIONS

<b>Print resolution</b>	1,800 (equivalent) x 600 dpi, 1,200 x 1,200 dpi
<b>Page description language</b>	PCL 6 (XL3.0), PCL 5c, PostScript 3 (CPSI 3016), XPS
<b>Operating systems</b>	Windows 7 (32/64), Windows 8.1 (32/64), Windows 10 (32/64), Windows Server 2008 (32/64), Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Macintosh OS X 10.10 or later, Unix, Linux, Citrix
<b>Printer fonts</b>	80 PCL Latin, 137 PostScript 3 Emulation Latin
<b>Mobile printing</b>	AirPrint (iOS), Konica Minolta Print Service (Android), Konica Minolta Mobile Print (iOS/Android) Optional: Google Cloud Print, Wi-Fi Direct

## PRINTER SPECIFICATIONS (OPTIONAL)

<b>Print controller</b>	Embedded Fiery IC-420
<b>Controller CPU</b>	AMD GX-424CC @ 2.4 GHz
<b>Memory/HDD</b>	4 GB / 500 GB
<b>Page description language</b>	Adobe PostScript 3 (CPSI 3020), PCL 6, PCL 5c
<b>Operating systems</b>	Windows 7 (32/64), Windows 8.1 (32/64), Windows 10 (32/64), Windows Server 2008 (32/64), Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Macintosh OS X 10.10 or later, Linux

## SCANNER SPECIFICATIONS

<b>Scan speed</b>	Up to 140/140 ipm in simplex (mono/color) Up to 280/280 ipm in duplex (mono/color)
<b>Scan resolution</b>	Up to 600 x 600 dpi
<b>Scan modes</b>	Scan-to-eMail (Scan-to-Me), Scan-to-SMB (Scan-to-Home), Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Scan-to-URL, TWAIN scan
<b>File formats</b>	JPEG, TIFF, PDF, Compact PDF, Encrypted PDF, XPS, Compact XPS, PPTX Optional: Searchable PDF, PDF/A 1a and 1b, Searchable DOCX/PPTX/XLSX
<b>Scan destinations</b>	2,000 destinations + 100 groups, LDAP support

## COPIER SPECIFICATIONS

<b>Copy resolution</b>	600 x 600 dpi
<b>Gradation</b>	256 gradations
<b>Multicopy</b>	1-9,999
<b>Original format</b>	Max. 11" x 17"
<b>Magnification</b>	25-400% in 0.1% steps, Auto zoom

## FAX SPECIFICATIONS

<b>Fax standard</b>	Super G3 (optional)
<b>Fax transmission</b>	Analog, i-Fax, Color i-Fax, IP-Fax
<b>Fax resolution</b>	Up to 600 x 600 dpi
<b>Fax compression</b>	MH, MR, MMR, JBIG
<b>Fax modem</b>	Up to 33.6 Kbps
<b>Fax destinations</b>	2,000 single + 100 groups

## USER BOX SPECIFICATIONS

<b>Storable documents</b>	Up to 3,000 documents or 10,000 pages
<b>Type of user boxes</b>	Public, Personal (with password or authentication), Group (with authentication)
<b>Type of system boxes</b>	Secure print, Encrypted PDF print, Fax receipt, Fax polling

## SYSTEM FEATURES

<b>Security</b>	ISO 15408 HCD-PP Common Criteria (in evaluation), IP filtering and port blocking, SSL3 and TLS1.0/1.1/1.2 network communication, IPsec support, IEEE 802.1x support, User authentication, Authentication log, Secure print, Kerberos, Hard drive data encryption (AES 256), Confidential fax, Print user data encryption Optional: Antivirus scanning (Bitdefender™), Copy protection (Copy Guard, Password Copy)
<b>Accounting</b>	Up to 1,000 user accounts, Active Directory support (user name + password + e-mail + smb folder), User function access definition, Authentication by mobile device (Android) Optional: Biometric authentication (finger vein scanner), ID card authentication (ID card reader), Authentication by mobile device (iOS)
<b>Software</b>	Net Care Device Manager, Data Administrator, Box Operator, Web Connection, Print Status Notifier, Driver Packaging Utility, Log Management Utility

<sup>1</sup> Warm-up time may vary depending on the operating environment and usage.

<sup>2</sup> Maximum monthly copy/print volume supported under standard vendor-supplied service defines the upper end of expected customer volume for the device. Customers should consider multiple machines if average monthly volume approaches duty cycle on a continual basis.

- All specifications refer to 8.5" x 11" paper of 80 g/m<sup>2</sup> weight.
- The support and availability of the listed specifications and functionalities vary depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of 8.5" x 11"). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Muratec does not warrant that any specifications mentioned will be error-free.

**Simitri HD**  
High Definition Polymerised Toner

**SAP**® Printer Vendor Solution

Works with  
**Apple AirPrint**



For complete information on Muratec products and solutions, please contact: **469.429.3300** or visit **www.muratec.com**

© 2020 MURATEC AMERICA, INC. Muratec and the Muratec logo are trademarks and/or registered trademarks of Murata Machinery, Ltd. or its subsidiaries in the United States and other countries. Other names, such as those of products of other companies, are the trademarks or registered trademarks of their respective companies. All specifications subject to change without notice. Not all features and options available at the time of product launch.

**muratec**  
MURATEC AMERICA, INC.  
www.muratec.com

Muratec America, Inc.  
14800 Landmark Blvd., Suite 720, Dallas, TX 75254

**www.muratec.com**



Item #: MK-3295  
7/2020-Z